Clay Minerals, Ca/Mg Ratio and Fe-Al-Oxides in Relation to Structural Stability, Hydraulic Conductivity and Soil Erosion in Southeastern Turkey

Kadir YILMAZ* Kahramanmaraş Sütçü İmam University, Department of Soil Science, Faculty of Agriculture, Kahramanmaraş - TURKEY İsmail ÇELİK, Selim KAPUR Çukurova University, Department of Soil Science, Faculty of Agriculture, 01330, Adana - TURKEY John RYAN International Center for Agricultural Research in the Dry Areas, P.O. Box 5466, Aleppo - SYRIA

Received: 13.02.2004

Abstract: Studies of clay mineralogy and related chemical composition are rarely connected with implications for soil management in the field. However, this study attempts to manifest the practical utilization of analytical data for determining the susceptibility to soil erosion. The data obtained involve the determination of clay mineral properties, calcium/magnesium ratios, and free aluminum (Al) and iron (Fe) oxides on structure stability, and hydraulic conductivity properties. Nine representative soil pedons developed on serpentine, limestone, and basalt parent materials were selected for the study. The soils were initially grouped into 3 according to their structural stability values. Group 1 soils had the lowest structural stability, highest smectite/kaolinite ratios, and shallow profile depths with the lowest Ca^{2+}/Mg^{2+} ratios. Group 2 soils had moderate structural stability and smectite/kaolinite ratios with moderate profile depths and the highest Ca^{2+}/Mg^{2+} ratios. Group 3 soils had the highest structural stability values, the lowest smectite/kaolinite ratios with deep profiles, moderate Ca^{2+}/Mg^{2+} ratios, and the highest free Al-Fe oxide contents with kaolinite ratios for structural stability studies in soils, and Ca^{2+} and Mg^{2+} contents, Ca^{2+}/Mg^{2+} ratios, and free Al-Fe oxides are indices reflecting erodibility (such as the shallow Group 1 soils) that should be considered more susceptible to erosion.

Key Words: Clay minerals, structural stability, hydraulic conductivity, erosion, calcium/magnesium ratio.

Kil Mineralleri, Ca/Mg Oranı ve Fe, Al Oksitlerin Strüktür Stabilitesi, Hidrolik İletkenlik ve Erozyon İlişkileri

Özet: Toprakların kil mineralojileri ve kimyasal yapıları ile ilgili çalışmalar, toprak yönetimi çalışmalarıyla çok seyrek olarak ilişkilendirilmişlerdir. Bu bağlamda, çalışılan toprakların erozyona duyarlılıklarının saptanması amaçlanarak, toprakların kil mineralleri özellikleri ve kalsiyum/magnezyum oranları ile serbest alüminyum ve demir içeriklerinin strüktür stabilitesi ve hidrolik iletkenlikleri ile ilişkileri araştırılmıştır. Bu amaçla farklı ana materyaller üzerinde oluşmuş topraklar çalışmada kullanılmışlardır. Bunlar serpantin, kireçtaşı ve bazalt ana materyalleri üzerinde oluşmuş topraklardır. İncelenen topraklar strüktür stabilitelerine göre üç grupta yer almaktadırlar. İlk grup topraklar siğ olup, en düşük strüktür stabilitesine, en yüksek smektit/kaolinit oranına ve en düşük Ca⁺²/Mg⁺² oranına sahiptirler. Buna karşın orta derinlikteki ikinci grup topraklar orta düzeyde strüktür stabilitesine ve smektit/kaolinit oranıyla birlikte en yüksek Ca⁺²/Mg⁺² oranına sahiptirler. Derin profilli üçüncü grup topraklar ise en yüksek strüktür stabilitesine, en düşük smektit /kaolinit oranına, orta düzeyde Ca⁺²/Mg⁺² oranına ve en yüksek Al-Fe oksit içeriğine sahiptirler. Birinci ve ikinci grup topraklarda baskın kil minerali kaolinittir. Elde edilen bulgularda, toprakların strüktür stabilitesinde; smektit/kaolinit oranının, Ca⁺², Mg⁺² içeriğinin, Ca⁺²/Mg⁺² oranının ve Al-Fe oksit içeriğini önemli olduğu saptanmıştır. Bu ölçütler toprakların erozyon ile aşınabilirliği üzerine önemli etki ettiğinden, sığ profilli birinci grup toprakların erozyona daha duyarlı olmaları nedeniyle, yönetim uygulamalarının dikkatle hazırlanmaları gerekliliğini ortaya koymaktadır.

Anahtar Sözcükler: Kil mineralleri, strüktür stabilitesi, hidrolik iletkenlik, erozyon, kalsiyum /magnezyum oranı.

^{*}Correspondence to: kyilmaz@ksu.edu.tr

Introduction

The chemical and mineralogical compositions of soil materials have a particular influence on the physical properties and soil erodibility of soils in dry climatic conditions (Birkeland, 1984; Reichert and Norton, 1994). An increase in clay does not always result in increased stability. While the clay mineral content is an important factor in aggregation, its influence is modified by the stability of high-clay soils, which depends on the physical-chemical properties of the clay (Warkentin, 1982; Reichert and Norton, 1994). Smectitic clays are more dispersible than kaolinitic clays (Goldberg and Glaubig, 1987) as well as illitic and kaolinitic soils, which contain small amounts of smectite that may be dispersible and as susceptible to sealing as smectitic soils (Stern et al., 1991). Kaolinitic soils have the greatest aggregate stability the montmorillonitic soils the lowest. The greater dispersivity of montmorillonite compared with that of kaolinite decreases the aggregate stability of montmorillonitic soils.

Soil loss through erosion is significantly lowest in the kaolinitic, highest in the montmorillonitic, and intermediate in the non-phyllosilicate soils. Kaolinitic soils, with the lowest soil loss, high aggregate stability, and low soil detachment and runoff transport capacity, are in contrast to montmorillonitic soils, with the lowest aggregate stability and the highest runoff, showing the greatest soil loss. For non-phyllosilicate soils, their intermediate aggregate stability and high runoff rates accounted for the intermediate material losses from these soils (Wakindiki and Ben-Hur, 2002). Six et al. (2000) indicated that free oxides and kaolinite clay minerals are important factors for the stability of soil aggregates. Laboratory studies using synthetic oxide precipitates have shown that AI and Fe oxyhydroxides promote aggregation (Oades, 1984). The structural stability shows the resistance of aggregates to breakdown in water and other external factors. Degradation of the soil structure decreases water permeability, reduces the biomass productivity of the soil, and increases erosivity. Shainberg and Singer (1991) showed that dispersion and deposition of swelling clays in narrow necks of conducting pores reduced the soil's hydraulic conductivity.

Dontsova and Norton (2002) demonstrated that high Mg^{2+} contents had adverse effects on soil structure and that the Mg^{2+} ion had less flocculating effects on soil clays than Ca^{2+} due to its larger hydrated radius; they also

found a significant negative relationship between the fraction of Mg^{2+} on the exchange sites and in the solution and the optical transmittance of the clay suspensions, indicating a lesser degree of flocculation of Mg^{2+} saturated clay. In addition, soil loss was increased significantly by Mg^{2+} , suggesting that erosion rates increased due to increasing soil erodibility and runoff as a result of exchangeable Mg^{2+} having contributed to surface sealing.

The objectives of this study were to determine the effects of (i) clay mineral properties, (ii) Ca^{2+}/Mg^{2+} ratio, and (iii) free oxides on structure stability, hydraulic conductivity, and erosion of a range of soils varying in clay mineral type and contents in southeastern Turkey.

Materials and Methods

The soils selected were high (Group 1, Profiles: 1, 2 and 3), moderate (Group 2, Profiles: 4, 5 and 6) and low (Group 3, Profiles: 7, 8 and 9) in smectite/kaolinite ratio. Nine representative soil pedons with different clay contents, and varying in Ca^{2+} , Mg^{2+} , Al-Fe free oxides and soil depth, were selected on serpentine (shallow) (55 cm) (Group 1), limestone (moderately deep) (80 cm) (Group 2) and basalt (deep) (123 cm) (Group 3) parent materials in southeastern Turkey. These profiles were developed under similar topography, vegetation, and climatic conditions.

Soil pH was determined in 1:2.5 soil/water suspensions (McLean, 1982). Exchangeable cations and cation exchange capacity (CEC) were determined by the sodium-ammonium acetate method and analyzed by atomic absorption spectrophotometry (Soil Survey Staff, 1993). Particle size distribution was determined by the hydrometer method (Bouyoucus, 1951). Aggregate analysis was performed on disturbed soil samples sieved through 4-mm mesh screens under air-dry conditions. Undisturbed soil samples of about 100 cm³ were used for the measurements of bulk density, hydraulic conductivity, and porosity. The dry bulk density, porosity and structural stability of aggregates were determined by the methods described by Blake and Hartge (1986), Danielson and Sutherland (1986) and Leo (1963), respectively. Saturated hydraulic conductivity was determined using undisturbed soil samples of 100 cm³ volume (Klute and Dirksen, 1986). The total porosity was determined in undisturbed water saturated samples of 100 cm³. Micropores were measured by determining the volumetric water contents, using a pressure membrane apparatus at field capacity. Macropores were calculated as the difference between the total porosity and micropores.

The total carbonate contents were measured using a Scheibler calcimeter (Allison and Moodie, 1965). Organic matter was determined by the Walkley-Black wet oxidation method (Allison, 1965). For the determination of oxides (Al_2O_3 , Fe_2O_3) soil samples (<2 mm) were treated with citrate-bicarbonate-dithionite (CBD) (Jackson, 1969). Aluminum and iron oxides were determined using the methods described in Jackson (1969) and Hsu (1963), respectively.

Clay minerals were determined in surface and subsurface horizons of all the profiles. The soil samples for mineralogical analysis were pre-treated with 1 N NaOAC, adjusted to pH 5, to remove carbonates, and with 30% H_2O_2 to remove organic matter, and with sodium dithionite-citrate-bicarbonate to remove Si-Al-Fe oxides (Jackson, 1969). The soils were then adjusted to pH 9.5 with 1 M Na₂CO₃ for dispersion. The sand fraction was separated by wet sieving, and clay and silt fractions were separated by sedimentation and decantation (Jackson,

1969). Diffractograms were obtained from Mg- and Ksaturated clay slides by scanning from 3 to 13 20, with nickel-filtered Cu K α radiation using a Philips X-ray diffractometer (Jackson, 1969). The diffraction intensity of the clay minerals was determined by calculating the peak areas. Vermiculite minerals were determined by the differences between Mg- and K-saturated clay slides at the 10 Å peak. The multiplication factors determined by Yılmaz (1990), and Yılmaz and Sayın (1998) for the Harran and Çukurova Plain soils, respectively, were used for quantitative clay analysis. According to both studies, the multiplication factors were 3.37 for smectitepalygorskite, 2.25 for smectite-illite and 3.29 for smectite-kaolinite. Duncan's multiple range statistical tests were used for comparing the means (Hays, 1988).

Results and Discussion

The physical, chemical and mineralogical distributions of the soils are presented in Tables 1, 2 and 3, respectively. For the 9 soils studied, the structural stability values were divided into 3 groups. Group 1 soils had the lowest structural stability, whereas Group 2 and Group 3 soils had intermediate and the highest values

Levels	Particle Size Distribution (%)			Bulk	Hydraulic		Structural		
	Sand	Silt	Clay	(Mg m ⁻³)	(cm h ⁻¹)	Total	Micro	Macro	Stability
			GRO	UP 1 (Smectite	e/Kaolinite: 7.8	1)			
Max.	44	40	37	1.41	3.3	69	40	34	36
Min.	27	29	25	1.00	0.7	54	35	18	21
Mean	33a	34	33b	1.15	1.8a	62a	37	24a	27b
			GRO	UP 2 (Smectite	e/Kaolinite: 1.26	5)			
Max.	17	36	65	1.26	2.3	66	40	28	66
Min.	6	27	47	1.02	0.2	55	33	17	42
Mean	10b	31	59a	1.13	1.0b	62a	38	24a	56a
			GRO	UP 3 (Smectite	e/Kaolinite: 0.49	9)			
Max.	12	39	64	1.55	3.4	67	50	28	69
Min.	7	28	49	1.04	0.1	44	30	8	53
Mean	9b	32	59a	1.27	1.2b	55b	40	16b	62a
	***	NS	***	NS	***	*	NS	*	***

Table 1. The physical properties of the soils.

Mean separation within columns by Duncan's multiple range tests, $\mathsf{P} \leq 0.05$

NS, ***, **, *Non-significant or significant at P \leq .001, 0.01 and 0.05, respectively

Levels	рН (1:2.5)	Organic Matter	CaCO ₃	Free Al ₂ O ₃	Free Fe ₂ O ₃	CEC (cmol kg ⁻¹)	Exchangeable Cations (cmol kg ⁻¹)				- 2, 2,
			(%)			Na ⁺	K+	Ca ²⁺	Mg ²⁺	Ca ²⁺ /Mg ²⁺
				GRO	UP 1 (Smec	tite/Kaolinite: 7	7.81)				
Max.	7.1	4.3	3.5	2.71	0.80	35.3	0.14	1.70	11.08	28.37	1.03
Min.	6.8	1.2	0.3	1.11	0.57	19.3	0.04	0.36	4.05	10.73	0.23
Mean	6.9ab	2.4	1.1b	1.88	0.63	23.7b	0.07	0.76	7.26c	15.64a	0.53b
				GRO	UP 2 (Smec	tite/Kaolinite: 1	.26)				
Max.	7.7	3.4	48.1	2.46	0.96	64.2	0.08	1.78	58.28	8.64	15.34
Min.	7.5	1.4	6.5	0.43	0.46	45.1	0.03	0.52	41.38	2.70	4.88
Mean	7.6a	2.4	17.6a	1.59	0.61	56.5a	0.05	1.15	49.63a	5.69b	10.41a
				GRO	UP 3 (Smec	tite/Kaolinite: C).49)				
Max.	7.5	3.2	3.7	5.01	1.22	66.7	0.08	1.20	54.10	11.61	4.93
Min.	5.2	0.8	0.2	0.73	0.30	10.3	0.05	0.17	6.23	2.83	0.82
Mean	6.5b	1.9	1.2b	2.49	0.70	33.1b	0.07	0.88	25.09b	7.03b	3.08b
	**	NS	***	NS	NS	**	NS	NS	***	**	***

Table 2. The chemical properties of the soils.

Mean separation within columns by Duncan's multiple range tests, $P \leq 0.05$

NS, ***, **, *Non-significant or significant at P \leq 0.001, 0.01 and 0.05, respectively

Profile Clay Fraction Levels Smectite Illite Kaolinite Vermiculite Depth Paligorskite (cm) (%) GROUP 1 (Smectite/Kaolinite: 7.81) Max 65 18.58 4.85 3.50 2.58 1.39 Min 43 10.56 3.13 1.40 1.53 0.73 55 16.01a 3.72c 2.45c 2.05c Mean 1.15b GROUP 2 (Smectite/Kaolinite: 1.26) 7.56 Max 105 17.90 12.74 8.98 12.19 2.07 Min 65 11.27 5.37 9.78 11.14 13.98a 4.62a Mean 80 11.99b 7.12b 11.09b GROUP 3 (Smectite/Kaolinite: 0.49) 150 15.97 16.88 4.62 Max 8.48 15.95 Min 100 5.38 12.40 9.89 10.63 2.04 3.35a Mean 123 7.05b 14.11a 13.51a 14.37a *** *** *** *** **

Table 3. The mineralogical distributions of the soils.

Mean separation within columns by Duncan's multiple range tests, $\mathsf{P} \leq 0.05$

NS, ***, **, *Non-significant or significant at $P \leq 0.001,\,0.01$ and 0.05, respectively

(Table 1). The soils with the highest structural stability contained the highest kaolinite content and the lowest smectite/kaolinite ratio (Table 3). Group 1 soils were determined to have the lowest structural stability due to the highest smectite/kaolinite ratios and the lowest Ca^{2+}/Mg^{2+} rates. In addition, the coarser textures of Group 1 soils most probably contributed to the development of low structural stabilities. The lowest structural stability values of Group 1 soils were indicated by the coarse textures and low Ca^{2+}/Mg^{2+} rates (Table 2) and also shown by the highly negative correlation between structural stability and sand, and the positive clay content (Figures 1a,b). Similarly, Kemper and Koch

(1966) found that aggregate stability increased with increasing clay contents.

However, an increase in clay does not always yield an increase in stability, since the clay mineral content of a soil is an important factor in aggregation, and the stability of high-clay soils depends on the physical-chemical properties of the clays (Warkentin, 1982). A significant positive correlation was found between kaolinite contents and structural stability, whereas significant negative correlations were found between smectite contents and structural stability, and between smectite/kaolinite ratios and structural stability (Figures 1c,d,e). These indicated that clay types and contents of the investigated soils had



Figure 1. The relationship between clay types and structural stability index (SSI).

important effects on structural stability. Although the organic matter content and soil texture of Group 2 and Group 3 soils were similar, their structural stability values were significantly different. Hence, Group 2 soils had a higher cation exchange capacity and pH because of higher smectite contents than Group 3 soils, which most probably form at high pH and cation exchange capacity, whereas kaolinite forms at lower pH conditions and low cation exchange capacity (Sayın, 1999).

A significant negative correlation was also found between smectite + vermiculite/kaolinite ratios and structural stability (Figure 1f). Thus, swelling smectite and vermiculute clays had dispersivity effects on soil structure, whereas kaolinite had a positive effect on structure due to its low swelling capacity; thus, the former was more susceptible to erosion as shown earlier by Reichert and Norton (1994), Singer (1994), Buhmann et al. (1996), Seta and Karathanasis (1996), and Wakindiki and Ben-Hur (2002). Similar results to this paper were shown by Singer (1994), indicating decreasing aggregate stabilities with increasing smectite and inversely with kaolinite content. The high flocculation capacity of kaolinite is due to the electrostatic interaction between the positive charges on the edges of the clay platelets and the negative charges in the body of the crystal (El-Swaify, 1980; Dixon, 1989).

In addition to the stabilizing effects of Fe and Al oxides and kaolinite by themselves, interactions between the 2 components have been reported (El-Swaify, 1980; Seta and Karathanasis, 1996). Group 3 soils have the highest free Al_2O_3 and Fe_2O_3 contents, positively affecting structure stability, as indicated by Reichert and Norton (1994), who determined the highest increase in aggregate stability in soils rich in kaolinite and Fe-Al

oxyhyroxides. Further adsorption of Fe and Al oxides on the few negatively charged sites of kaolinite reduces its cation exchange capacity and increases its positive charge (Dixon, 1989). Therefore, this interaction between Fe and Al oxides and kaolinite is synergistic and increases the aggregation potential of kaolinite.

Since Group 3 soils were highly weathered, kaolinite was the dominant clay mineral (Table 3), and Fe-Al free oxides of this soil were higher than those of Group 1 or 2 soils. The high Fe-Al free oxides and dominant kaolinite clay mineral of Group 3 soils caused increasing structural stability. In addition, the reason for the high structure stability of Group 2 soils may be the high CaCO₃ contents correlating with the structural stability (Table 2; Figure 2a) increasing with soil depth. Group 3 soils, with the highest mean soil depth (123 cm), were determined to have the highest structural stability, whereas Group 2 soils, with moderate depth (80 cm), were determined to have moderately high structural stabilities, with the lowest values obtained in Group 1 soils with probable high soil losses (55 cm) (Table 2). Thus, Group 1 soils are more vulnerable to erosion than the soils of Groups 2 and 3, with their corresponding lowest structural stability and thinner/shallower A and B horizons along with the highest smectite/kaolinite contents compared with Groups 2 and З.

Significant statistical variances were determined between the Ca²⁺/Mg²⁺ ratios and the soil groups (Table 2). The negative correlation between the structure stability and Mg²⁺ contents (Figure 2b), and the positive correlation of the Ca²⁺/Mg²⁺ ratios (Figure 2c) were similar to Dontsova and Norton's (2002) low Ca²⁺/Mg²⁺ ratios and high Mg²⁺ contents causing dispersion in soils that had different mineralogical compositions. For all soil



Figure 2. The relationship between exchangeable cations and structural stability index (SSI).

clays, a negative linear relationship was determined between the Mg^{2+} percentage in solution and the optical transmittance of clay suspension as an indicator of clay flocculation, documenting increased surface sealing and erosion (Dontsova and Norton, 2002). Keren (1991) also established that Mg^{2+} in soil could affect erosion rates, explained by the hydration number of the Mg^{2+} ion being about 50% greater than that of the Ca^{2+} ion.

Group 1 soil had the lowest Ca^{2+}/Mg^{2+} ratios and highest Mg^{2+} contents along with dominant smectite at the surface horizons compared with the Group 2 and 3 soils. Thus, the low Ca^{2+}/Mg^{2+} ratios, high Mg^{2+} contents, and dominant smectite caused dispersion in Group 1 soils. Saturated hydraulic conductivities of the surface soils of Group 1 (0.73 cm h⁻¹) were 3 to 4 times lower than those of the subsurface horizons (2.36 cm h⁻¹) (Figure 3). This is most probably due to the dominant smectite and Mg^{2+} contents, as well as the low Ca^{2+}/Mg^{2+} ratios in Group 1 soils.

Saturated hydraulic conductivity values were higher in Group 1 soils that have coarse texture and macroporosity than the Group 2 and 3 soils that have a fine texture (Table 1). Texture variation between Group 1 and Groups 2 and 3 was found at the 0.1% significance level. Hydraulic conductivities of Group 2 and Group 3 soils were present in the same statistical group and similar



Figure 3. Variation in hydraulic conductivity (HC) with soil depth.

texture, whereas the hydraulic conductivity of Group 3 soils was higher than that of Group 2 soils (Table 1). The structural stability variation with the organic matter contents was non-significant in all soils, indicating the significance of soil texture and clay types on the hydraulic conductivity of soils. Group 1 soils had higher hydraulic conductivity values than Group 2 and Group 3 soils due to the coarser textures and higher macroporosity of the latter.

The differences in the hydraulic conductivities of Group 2 and Group 3 soils with similar texture were explained by the differences in clay mineralogy, free Al-Fe oxide levels and structural stability. Namely, Group 2 soils had higher smectite and smectite/kaolinite ratios, and lower free Al-Fe oxides and structural stability than Group 3 soils. The higher smectite contents were negatively associated with the hydraulic conductivity of Group 2 soils. Group 3 soils had higher kaolinite contents and lower smectite/kaolinite ratios with higher Al-Fe oxide contents than Group 2 soils, and accordingly higher hydraulic conductivity and structural stability values than Group 2 soils. Similar results between the clay mineralogy and hydraulic conductivity were found by Romkens et al. (1995), and Mermut et al. (1997), concluding that the presence of more smectite clay in the soil resulted in a rapidly decreasing infiltration rate despite the high organic matter contents.

Thus, this study, together with previousones, revealed that the high hydraulic conductivity of Group 1 soils is associated with coarser textures, whereas, as in Group 1, the higher hydraulic conductivity values of soil groups with similar textures is explained by the differences in the clay types. However, the values of hydraulic conductivity and structural stability of Group 1 and Group 2 soils varied despite their dominant clay types. This was most probably due to differences in the texture of the soils of Groups 1 and 2.

The bulk density of the Group 1 and Group 2 soils was similar, unlike that of Group 3 soils. The lowest organic matter, total porosity and highest free Fe_2O_3 were in Group 3 soils that had the greatest bulk density. The significant correlation found between the bulk density and organic matter, total porosity and free Fe_2O_3 (Figures 4a,b,c) suggests that the bulk density of the soils was reduced by the organic matter content of the soils and increased by free Fe_2O_3 . High bulk densities indicated compaction and decreasing macroporosity in the soils



Figure 4. The relationship between bulk density, organic matter, total porosity, and iron oxides.

(Table 1). Zebarth et al. (1999) and Aggelides and Londra (2000) found that increasing organic matter caused a decrease in bulk density and that organic matter contents, free Fe_2O_3 , and mineralogical compositions affected the bulk densities of similar soils.

Conclusion

The structural stability values of the 9 soils studied from southeastern Turkey were negatively affected by an increasing smectite/kaolinite ratio. Statistically significant positive relationships were found between structural stability and kaolinite, and there was a negative relationship with smectite. The structural stability values

References

- Aggelides, S.M. and P.A. Londra. 2000. Effect of compost produced from town wastes and sewage sludge on the physical properties. Bioresource Tech. 71: 253-259.
- Allison, L.E. 1965. Organic carbon. Walkley-Black Method. In: Methods of Analysis, (Ed. C.A. Black), Agronomy Monograph, No. 9. Part 2. American Society of Agronomy. Madison, Wisconsin, USA, pp. 1367-1378.
- Allison, L.E. and C.D. Moodie. 1965. Carbonate volumetric calcimeter method. In: Methods of Analysis, (Ed. C.A. Black), Agronomy Monograph. No. 9. Part 2. American Society of Agronomy. Madison, Wisconsin, USA, pp. 1389-1392.
- Birkeland, P.W. 1984. Soils and Geomorphology. Department of Geological Sciences, University of Colorado. Oxford University Press, New York, Oxford.
- Blake, G.R. and K.H. Hartge. 1986. Bulk density. In: Methods of Soil Analysis, (Ed: A. Klute) Agronomy Monograph. No. 9. Part 1, ASA and Soil Science Society of America, Madison, Wisconsin, USA, pp. 363-375.

of the soils were also positively affected by the increasing ratio of Ca^{2+}/Mg^{2+} , and Al-Fe oxide contents, i.e. significant positive relationships were determined with increasing Ca^{2+} and Al-Fe oxides and negative relationships with increasing Mg^{2+} . These point to the need for utmost care against erosion in the management of shallow soils such as Group 1.

This study also revealed that high hydraulic conductivity is associated with coarser textures, differences in clay mineralogy, free Al-Fe oxide levels and structural stability. The lowest amounts of palygorskite, illite and kaolinite corresponding to the highest hydraulic conductivity values may point out some relations to be considered for sustainable soil and water management.

- Bouyoucos, G.J. 1951. A recalibration of the hydrometer method for making mechanical analysis of soils. Agron. Jour. 43: 434-438.
- Buhmann, C., I. Rapp and M.C. Laker. 1996. Differences in mineral ratios between disaggregated and original clay fractions in some South African soils as affected by amendments. Aust. J. Soil Res. 34: 909-923.
- Danielson, R.E. and P.L. Sutherland. 1986. Porosity. In: Methods of Soil Analysis, (Ed: A. Klute), Agronomy Monograph. No. 9. Part 1, ASA and Soil Science Society of America, Madison, Wisconsin, USA, pp. 443-461.
- Dixon, J.B. 1989. Kaolin and serpentine group minerals. In: Minerals in Soil Environments, (Ed: J.B. Dixon and S.B. Weed) Soil Science Society of America Book Series 1, Madison, Wisconsin, USA, pp. 467-525.
- Dontsova, K.M. and L.D. Norton. 2002. Clay dispersion, infiltration, and erosion as influenced by exchangeable Ca and Mg. Soil Sci. Soc. Am. J. 167: 184-193.

- El-Swaify, S.A. 1980. Physical and mechanical properties of oxisols. In: Soils with Variable Charge, (Ed: B.K.G. Theng), Offset Publ. Palmerston North, NZ. pp. 303-324.
- Goldberg, S. and R.A. Glaubig. 1987. Effect of saturation cation, pH, and aluminum and iron oxide on the flocculation of kaolinite and montmorillonite. Clays Clay Min. 35: 220-227.
- Hays, L.W. 1988. Statistics. 4th edition, Holt, Rinehart and Winston Inc., London.
- Hsu, P.H. 1963. Effect of initial pH, phosphate, and silicate on the determination of aluminium with aluminon. Soil Sci. 96: 230-238.
- Jackson, M.L. 1969. Soil chemical analysis. Advanced course. 2nd ed. published by the author. Univ. of Wisconsin. Madison. USA.
- Kember, W.D. and E.K. Koch. 1966. Aggregate stability of soils from western United States and Canada. Colorado Agric. Exp. Stn. Bull. no: 1355: 1-52. Agric. Res. Service, USDA, and Colorado Agric. Exp. Stn., Fort Collins, CO., USA.
- Keren, R. 1991. Specific effect of magnesium on soil erosion and water infiltration. Soil Sci. Soc. Am. J. 55: 783-787.
- Klute, A. and C. Dirksen. 1986. Hydraulic conductivity and diffusivity, Laboratory methods. In: Methods of Soil Analysis, (Ed: A. Klute) Part 1, Agronomy Monograph. 9. ASA and Soil Science Society of America, Madison, Wisconsin, USA, pp. 687-734.
- Leo, M.A. 1963. A rapid method for estimating structural stability of soils. Soil Sci. 96: 342-346.
- McLean, E.O. 1982. Soil pH and lime requirement. In: Methods of Soil Analysis, 2nd ed. (Ed: A.L. Page et al.) Part 2. Agronomy Monograph. No. 9. ASA, Madison, Wisconsin, USA, pp. 199-224.
- Mermut, A.R., S.H. Luk, M.J.M. Romkens and J.W.A. Poesen. 1997. Soil loss by splash and wash during rainfall from two loess soils. Geoderma. 75: 203-214.
- Oades, J.M. 1984. Interaction of polycations of Al and Fe with clays. Clays Clay Miner. 32: 49-57.
- Reichert, J.M. and Norton, L.D. 1994. Aggregate stability and rainimpacted sheet erosion of air-dried and prewetted clayey surface soils under intense rain. Soil Sci. 158: 159-169.
- Romkens, M.J.M., S.H. Luk, J.W.A. Poesen and A.R. Mermut. 1995. Rainfall infiltration into loess soils from different geographic regions. Catena. 25: 21-32.

- Sayın, M. 1999. Soil mineralogy. Çukurova University, Agriculture Faculty, no: 227, A72. Adana, Turkey (in Turkish) pp. 69-86.
- Seta, A.K and A.D. Karathanasis. 1996. Water dispersible colloids and factors influencing their dispersibility from soil aggregates. Geoderma. 74: 255-266.
- Shainberg, I. and M.J. Singer. 1990. Soil response to saline and sodic conditions. In: Agricultural Salinity Assessment and Management, (Ed: K.K. Tanji) Am. Soc. Civil Eng., St. Josephs, USA, p: 91-112.
- Singer, A. 1994. Clay mineralogy as affecting dispersivity and crust formation in aridisols. In: Transactions of the 15th World Congress of Soil Science, (Ed: J.D. Etchevers), Acapulco, Mexico. Vol 8a. Int. Soc. Soil Sci. and Mexican Soc. Soil Sci., Acapulco, Mexico, p: 37-46.
- Six, J., E.T. Elliott and K. Paustion. 2000. Soil structure and soil organic matter: II. A normalized stability index and the effect of mineralogy. Soil Sci. Soc. Am. J. 64: 1042-1049
- Soil Survey Staff. 1993. Soil survey manual. USDA handbook No. 18. Washington, USA.
- Stern, R., M. Ben-Hur and I. Shainberg. 1991. Clay mineralogy on rain infiltration, seal formation and soil losses. Soil Sci. 152: 455-462.
- Wakindiki, I.I.C. and M. Ben-Hur. 2002. Soil mineralogy and texture effects on crust micromorphology, infiltration, and erosion. Soil Sci. Soc. Am. J. 66: 897-905.
- Warkentin, B.P. 1982. Clay soil structure related to soil management. Trop. Agric. (Trinidad). 59: 82-91.
- Yılmaz, K. 1990. The properties of Harran plain soils. Soil Science Department, Natural Applied Sciences, Çukurova University, Adana, Turkey (PhD Thesis) pp. 54-89.
- Yilmaz, K. and Sayın, M. 1998. The quantitative clay analysis with multiplication factor on soil series of Çukurova Region. J. Sci. Eng., Kahramanmaraş Sütçü İmam University, Kahramanmaraş, Turkey, 2: 36-46.
- Zebarth, B.J., G.H. Neilsen, E. Hogue and D. Neilsen. 1999. Influence of organic waste amendments on selected soil physical and chemical properties. Canadian J. Soil Sci. 79: 501-504.